



## **DELUXE OVERSIZE DOUBLE ARM REPAIR STAND PRS-2 OS**

<b>Ref. No.</b>	<b>Part No.</b>	<b>Description</b>	<b>Qty.</b>	<b>Ref. No.</b>	<b>Part No.</b>	<b>Description</b>	<b>Qty.</b>
1	138	Handle grip	2	15	114S	Unthreaded lock block	3
2	103S	Handle	2	16	109S	Spring pin 5/32 x 1-1/4	3
3	107S-2	Pin with washers and circlips	4	17	112S	Lock block bolt assembly	3
4	101-3	Movable jaw	2	18	111S	Handle	3
5	468B	Jaw cover set (incl. circlips)	2	19	110S	Ball knob	3
6	102-3	Rotating shaft	2	180		Lock block assy. (#13-19)	
7	108S-2	Pin with washers and circlips	2	20	123-2	Solid pin	1
8	117S-1	Eyebolt	2	21	124-2	Support weldment	1
9	118S	Adjusting barrel	2	22	105	Oversize work tray complete	1
10	121S	Adjusting barrel pivot	2	23	125-2	Base support weldment	1
11	136	Nut 1/4 - 28	2	24	131S	Nut 1/4 - 20	4
	122S	Linkage assembly (#8-11)		25	132S	Washer 3/16" USS	4
12	116S	Cap screw	4	26	135	Base	1
13	113S	Threaded lock block	3	27	133S	Cap screw 1/4 - 20 x 7/8	4
14	115S	Spring	2				

NOTE: Because of design changes made to the 100-3C Clamp, replacement of a #102-3 Rotating shaft manufactured prior to Jan. 2001 also requires replacement of the #103S Handle. A #102-3 manufactured prior to Jan. 2001 will have a protrusion (approx. 21mm x 9mm x 8mm) on the shaft. A #102-3 manufactured after Jan. 2001 will not have this protrusion.